

# RITE-WEIGH OPEN-MOUTH BAGGER

Automatic high-speed, net weighing  
open-mouth bagging scale.



**DESIGN FEATURES:**

Reliable accuracies: +/- 1/4 of 1% obtainable with good product flow and consistent bulk density.

Speeds up to 25 bags per minute depending on product characteristics.

Versatile - will handle granulars, flakes, powders, feeds, chemicals, pellets, chunks and mixes.

Available with various sized weigh buckets.

<b>STANDARD SPECIFICATIONS:</b>	<b>OPTIONS:</b>
<b>CONSTRUCTION:</b> heavy-duty mild steel with one coat industrial primer and one coat paint.	<b>CONSTRUCTION:</b> T304 stainless steel on contacting surfaces.
Load cell weighing with preset digital weight controller.	Air-operated bag clamps available with auto-start and bag-in-place interlock.
<b>WEIGH BUCKETS:</b> 1, 1.5, 2, 2.5 or 3 cubic ft sizes.	Belt feeder for materials that have poor flow characteristics or tend to bridge.
NEMA 12 electrical controls (dust tight).	Vibratory feeder on the dribble stage for increased accuracies.
Two-stage feed producing a bulk & dribble flow effect for achieving greater accuracy.	<b>PAINT:</b> stainless steel.
Gravity feed with adjustable flow control (for free flowing materials).	NEMA 4 electrical controls (water tight).
<b>UTILITY REQUIREMENTS:</b>	NEMA 9 electrical controls (dust explosion proof).
Electrical: 115 V, 60 Hz, single-phase Pneumatic: 15 cfm @ 80 psi	

For more information contact:

**HUNTSMAN, INC.**

2362 Warren Ave., Twin Falls, ID 83301  
Ph: (888) 812-3377 Fax: (208) 733-2240