

HEAT SEALERS

FISCHBEIN

Manual Table top Impulse Heat Sealer

Features:

Manually Controlled.

Three sealing widths: 200 300 and 400 mm.

Equipped with adjustable electronic timers ranging from 0 to 1.4 seconds.

Sealing time is indicated by means of a signal light.

Width of Seal: 2 mm.

Sealing capacity ranges from 2 x .01 to 2 x .10 mm.

Available in 110 and 220 volts.



Model Number	Sealing Width
CD 200-110	200 mm
CD 200-220	200 mm
CD 300-110	300 mm
CD 300-220	300 mm
CD 400-110	400 mm
CD 400-220	400 mm

Manual Pedestal Mounted Impulse Heat Sealer

Features:

Pedestal mounted with tow position adjustments for sitting or standing operation (optional).

Three sealing widths: 300, 450 and 600 mm.

Adjustable electronic timer with illuminated control panel. Max. sealing time: 1.8 seconds.

Sealer jaws adjustable up to 40 mm for easy introduction of bag top.

Width of seal: 2 mm.

Sealing capacity ranges from 2 x .01 to 2 x 15 mm.

Available in 110 and 220 Volts.



Model Number	Sealing Width
CF 300-110	300 mm
CF 300-220	300 mm
CF 460-110	450 mm
CF 460-220	450 mm
CF 600-110	600 mm
CF 600-220	600 mm

Manual Pedestal Mounted Heat Sealer

Features:

Pedestal mounted with tow position adjustments for sitting or standing operation (optional).

Three sealing widths: 200, 300 and 450 mm.

Adjustable electronic timer with illuminated control panel.

Sealer jaws adjustable from 10 to 25 mm for easy introduction of bag top.

width of seal: 15 mm.

Sealing capacity ranges from 2 x .01 to 2 x .30 mm.

Available in 110 and 220 volts.



Model Number	Sealing Width
CP 20-110	200 mm
CP 20-220	200 mm
CP 30-110	300 mm
CP 30-220	300 mm
CP 45-110	450 mm
CP 45-220	450 mm

***Remember Huntsman, Inc. for all of
Your processing and packaging needs!!!***

Huntsman, Inc.

2362 Warren Ave. Twin Falls, ID 83301

Sales line: (888) 812-3377 Fax: (208) 733-2240

Visit us on the web at www.huntsmaninc.com

or e-mail us at mail@huntsmaninc.com