

PLASTIC LIQUID HOUSINGS

- Process Water Protection
- Low Cost- High Flow Rates
- Accepts Standard DOE Cartridges
- Light Weight
- Ideal For Well Water Applications
- All Plastic Eliminates Corrosion



The 718 and 720 series filter housings are manufactured from a durable polypropylene or clear Styrene-Acrilonitrile (SAN). Reinforced polypropylene housings have excellent chemical resistance and are ideal for many residential, commercial, and industrial applications. Clear sumps are manufactured from a clear, FDA complaint Styrene-Acrilonitrile (SAN). They offer on-site examination of the cartridge and have excellent compatibility as well.

The Model 720BH (High Temperature / High Pressure) is made of glass reinforced nylon resin. They have a maximum temperature of 200°F at 200 PSIG.

PRINCIPLE SPECIFICATIONS

Housing Model	718	718B	720	720B
Port Size	3/8"	3/8"	3/4"	3/4"
Maximum Temperature (°F)	125	125	125	125
Maximum Pressure (psig)	125	125	125	125
Maximum Flow Rate (GPM)	5	5	10	10
Principle Dimensions: (inches)				
Head diameter	4.625	4.625	5.125	5.125
Length	6.875	6.875	12.25	12.25
Removal of element	5.75	5.75	10.75	10.75
Filter Element Codes:				
Spun Polypropylene (1)	LE-718-□	LE-718-□	LE-720-□	LE-720-□
Pleated Element (2)	LE-718-□PL	LE-718-□PL	LE-720-□PL	LE-720-□PL
Materials Of Construction:				
Head & Internals	Polypropylene	Polypropylene	Polypropylene	Polypropylene
Bowl	Styrene-Acrilonitrile	Polypropylene	Styrene-Acrilonitrile	Polypropylene
O-Rings	Buna-N	Buna-N	Buna-N	Buna-N
Accessories:				
Mounting Bracket	MB720	MB720	MB720	MB720
O-Ring Set - Buna-N	GB720	GB720	GB720	GB720

Notes: (1) Micron Sizes available on the Spun Polypropylene Elements are 1, 5, 25, 50, 75, 150.
 (2) Micron Sizes available on the Pleated Elements are 0.5, 2, 10, 25, 50, 90



Huntsman, Inc. • 2362 Warren Ave • Twin Falls, ID 83301
(208) 733-2214 • Toll Free: (877) 733-2214 • Fax: (208) 733-2240
www.huntsmaninc.com • mail@huntsmaninc.com